

# High cut boot. engineered for extreme environments.

Designed to offer maximum protection, comfort and durability.





Anti-puncture



Anti-smash



Anti-static



Wear resistant



Anti-slip



Dustproof



Waterproof



Oil-resistant

Regulation (EU) 2016/425 EN ISO 20345:2022+A1:2024

S3 SRC

FortiSec. Web: www.fortisecppe.com Email: sales@fortisecppe.com







## CLASSIC-M211

### **PED932**

#### Tehnical details

Component	Description
Тоесар	Anti-smash steel toe - 80mm width(for size 42)- Resistant to an impact with an energy of 200 Joules.
Midsole	Perforation-resistant Non-Metallic Anti-Penetration insert - 1100 N compression protection.
Upper	Water penetration & absorption embossed leather thickness 1.4mm to 1.6mm
Lining	Water vapour permeable polyester sandwich mesh with abrasion resistance.
Insole	Made in solid material breathable mesh and 3mm thickness EVA with antistatic Z shape stitching line.
Outsole	Slip resistant,oil resistant dual desity PU sole with good abrasion resistance.
Size	EUR 36-47

#### **Logistics Information**

Packing Specification	Details
Net Weight	570g/piece
Inner Box Measurement	33x24x12cm
Carton Measurement (10 pairs/ctn)	61.5x46.5x35.5cm
20GP	3000 pairs
40GP	5400 pairs
40HC	6800 pairs
H.S code	64039900

FortiSec.
Web: www.fortisecppe.com
Email: sales@fortisecppe.com



