

High cut boot. engineered for extreme environments.

Designed to offer maximum protection, comfort and durability.





Anti-puncture



Anti-smash



Anti-static



Wear resistant



Anti-slip







Dustproof

Waterproof

Oil-resistant

Regulation (EU) 2016/425 EN ISO 20345:2022+1:2024

FortiSec. Web: www.fortisecppe.com Email: sales@fortisecppe.com







HEAVY DUTY-M701

PED26701

Tehnical details

Component	Description
Toecap	Anti-smash steel toe - 90mm width(for size 42) Resistant to an impact with an energy of 200 Joules.
Midsole	Perforation-resistant steel insert - 1100 N compression protection.
Upper	Water penetration & absorption embossed leather thickness 1.4mm to 1.6mm.
Lining	Water vapour permeable polyester sandwich mesh with abrasion resistance.
Insole	Made in solid material breathable mesh and 3mm thickness EVA with antistatic Z shape stitching line.
Lace	High durable polyester laces with length 130cm for size EUR 42.
Outsole	Slip resistant,oil resistant PU and rubber sole with good abrasion resistance.
Size	EUR 36-47

Logistics Information

Packing Specification	Details
Net Weight	700g/piece
Inner Box Measurement	34x20x12cm
Carton Measurement (10 pairs/ctn)	61.5x46.5x35.5cm
20GP	3000 pairs
40GP	5400 pairs
40HC	6800 pairs
H.S code	64034000

FortiSec.
Web: www.fortisecppe.com
Email: sales@fortisecppe.com



