

Low shoes with laces.

engineered for extreme environments.

Designed to offer maximum protection, comfort and durability.







Anti-puncture



Anti-smash



Anti-static



Wear resistant



Dustproof



Anti-slip



Oil-resistant

FortiSec.
Web: www.fortisecppe.com
Email: sales@fortisecppe.com







CLASSIC-L082 PED1213(0189-1)

Tehnical details

Component	Description
Тоесар	Anti-smash steel toe - 90mm width(for size 42)- Resistant to an impact with an energy of 200 Joules.
Midsole	Perforation-resistant steel insert-1100 N compression protection.
Upper	Water penetration & absorption suede leather thickness 1.4mm to 1.6mm.
Lining	Water vapour permeable polyester sandwich mesh with abrasion resistance.
Insole	Made in solid material breathable mesh and 3mm thickness EVA with antistatic Z shape stitching line.
Laces	High durable polyester laces with length 100cm for size EUR 42.
Outsole	Slip resistant,oil resistant dual desity PU sole with good abrasion resistance.
Size	EUR 36-47

Logistics Information

Packing Specification	Details
Net Weight	590g/piece
Inner Box Measurement	34x20x12cm
Carton Measurement (10 pairs/ctn)	61.5x41.5x35cm
20GP	3000 pairs
40GP	5400 pairs
40HC	6800 pairs
H.S code	64034000

FortiSec.
Web: www.fortisecppe.com
Email: sales@fortisecppe.com



